

EXPLORER 300

Portable Inmarsat BGAN terminal

COBHAM

2013 Data Sheet

The most important thing we build is trust



EXPLORER 300

Portable Inmarsat BGAN terminal

Compact - for individual usage

EXPLORER 300 makes it easy to stay connected anywhere in the world. It is complete broadband connectivity the size of a netbook.

It is ideal for single travelers who frequently change location, consisting of only one unit – a transceiver with an integrated antenna.

The smallest BGAN terminal

The smallest terminal in the EXPLORER series. Weighs only 1.4 kg. Dimensions: 16.8 x 21.7 x 5.2 cm.

Single User terminal

The ideal combination of performance and portability. Provides simultaneous high quality voice and broadband access at speeds up to 464 kbps. It supports LAN, USB, Bluetooth and phone/fax interfaces.

COBHAM

Compact and lightweight

Ideal if you primarily need voice, or moderate speed standard IP internet access.



Specifications

Dimensions

| | |
|------------------|---|
| Total H / W / D: | 168 / 217 / 52 mm 6.6 / 8.5 / 2.1 inches |
|------------------|---|

Weight (incl. battery): 1.4kg / 3.1lbs

Data capabilities

| | |
|---------------|----------------|
| Standard IP: | Up to 384 kbps |
| Streaming IP: | 32, 64 kbps |

Voice capabilities

| | |
|-----------------|------------------------|
| Standard voice: | 4 kbps |
| Premium voice: | 3.1 kHz audio, 64 kbps |

Text capabilities

| | |
|------|----------------|
| SMS: | 160 characters |
|------|----------------|

Inmarsat frequencies: 1525.0 – 1559.0 MHz (Rx)
1626.5 – 1660.5 MHz (Tx)

EIRP: 10dBW ±1dB

| | |
|------------------------|--|
| LCD display: | Graphical high resolution, back lit |
| User interface: | Four navigation keys and powerbutton Audio and LCD pointing aids. LED indicators. Thrane & Thrane web interface |
| Languages: | UK, FR, DE, ES, RU and CN |
| Approvals: | CE, FCC, GMPCS Inmarsat Class 3 Type Approval |

Interfaces

1 x Analogue RJ-11 phone / fax interface

1 x Bluetooth interface (Version 1.2)

| | |
|-------------------------|---|
| Antenna: | Integrated in transceiver unit |
| Frequencies: | 2400.0 – 2483.5 MHz |
| Max. coverage outdoor: | 25m / 82ft |
| Max. devices connected: | 1 handset, 1 PC/PDA |
| Profiles supported: | Cordless handset, serial port, service discovery application, dial-up networking, headset |
| Standard: | Power class 2 |

1 x LAN interface

| | |
|--------------------|--|
| Connector type: | RJ-45, MDI-X |
| Data rate: | 10/100 Mbps |
| Max. cable length: | 100m / 328ft (Cat5 UTP) |
| Standard: | ISO/IEC 8877:1992, and IEEE 802.3 (1998 edition) |

1 x BGAN SIM-Card slot

Environmental conditions

Temperature

| | |
|--------------------------|----------------------------------|
| Operational (ambient): | -25°C to +55°C / -13°F to +131°F |
| Storage (excl. battery): | -40°C to +80°C / -40°F to +176°F |

Battery storage temperature

| | |
|-----------|--------------------------------|
| 1 month: | -20°C / -4°F to +60°C / +140°F |
| 3 months: | -20°C / -4°F to +45°C / +113°F |
| 1 year: | -20°C / -4°F to +20°C / +68°F |

Relative humidity: 95% non-condensing at +40°C/+104°F

Robustness: 0.5 m/1.64 ft drop on concrete (operational, 95% survival)

Storage temperature: -40°C to +80°C (ex. battery)
-40°F to +176°F (ex. battery)

Water and dust: IP-54 (dust and spray proof)

Power

DC input range: 10-16VDC

Power consumption

| | |
|---------------------|-----------------------|
| Standby / transmit: | 0.8W / 14W (typical) |
| During charging: | 38W (max.) |
| Connector type | 2.5mm EIAJ RC-5320-IV |

AC/DC power supply

| | |
|---------|--------------------------|
| Input: | 100-240VAC, 47-63Hz, 50W |
| Output: | 15VDC |

Battery:

| | |
|----------------------------|----------------------------------|
| Lithium ion (rechargeable) | |
| Stand-by time: | 36h, 0°C/+32°F to 55°C/+131°F |
| Standard call: | 3h, 0°C/+32°F to 55°C/+131°F |
| Premium voice call: | 1h30m, 0°C/+32°F to +55°C/+131°F |
| Receive time, max.: | 3h30m @ 128kbps, (25°C / 77°F) |
| Transmit time, max.: | 2h15m @ 128kbps, |
| Min. number of charges: | 300 |
| Recharge time: | Less than 3 hours |
| Charge temperature: | 0°C / +32°F to +45°C / +113°F |

Other features

Phonebook; Fax; Message indicator; Traffic logging; Admin control (password protected); Webserver; Router or direct mode; Network Management; DHCP; Remote Management; Up to 11 x PDP context; Point-to-point Protocol over Ethernet (PPPoE).

Package

EXPLORER 300 terminal incl. rechargeable lithium ion battery LAN cable and 100-240VAC power supply.
Getting started kit - Quick start guide, CD with manuals.

Product number

403705A-00700 EXPLORER 300 Terminal

For further information please contact:

Cobham SATCOM
Lundtoftegaardsvej 93 D
DK-2800 Kgs. Lyngby
Denmark
www.cobham.com
Tel: +45 3955 8800
Fax: +45 3955 8888

